

BERKEBILE OIL CO INC -- 2 + 2 SPRAY SILICONE LUBRICANT, B303 -- 9150-00N072118

=====
Product Identification
=====

HS Ag Shop

Product ID:2 + 2 SPRAY SILICONE LUBRICANT, B303
MSDS Date:03/24/1995
FSC:9150
NIIN:00N072118
MSDS Number: CBXPQ
==== Responsible Party ====
Company Name:BERKEBILE OIL CO INC
Box:715
City:SOMERSET
State:PA
ZIP:15501-0175
Country:US
Info Phone Num:814-443-1656
Emergency Phone Num:814-443-1656;800-424-9300 (CHEMTREC)
Preparer's Name:T.J.S.
CAGE:FO088

==== Contractor Identification ====

Company Name:BERKEBILE OIL COMPANY, INC.
Box:715
City:SOMERSET
State:PA
ZIP:15501-0175
Country:US
Phone:814-443-1656
CAGE:FO088
Company Name:BERKEBILE OIL INC THE
Box:715
City:SOMERSET
State:PA
ZIP:15501-0175
Country:US
Phone:814-443-1656
CAGE:58011

=====
Composition/Information on Ingredients
=====

Ingred Name:RUBBER SOLVENT (NAPHTHA SOLVENT REFINED, LIGHT); (PETROLEUM
DISTILLATE). VP:100 @ 68F.
CAS:64741-84-0
Fraction by Wt: 76%
OSHA PEL:400 PPM (MFR)
ACGIH TLV:N/K

Ingred Name:PROPANE. VP:6350 @ 68F.
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN

Ingred Name:VENT:HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS & LEL
BELOW STATED LIMITS.
RTECS #:9999999ZZ

Ingred Name:EYE PROT:& FULL LENGTH FACESHIELD .
RTECS #:9999999ZZ

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT:LIQUID OR VAPOR CAN CAUSE MODERATE IRRITATION. SKIN CONTACT:CONTACT MAY DRY SKIN. PROLONGED CONTACT MAY CAUSE MODERATE IRRITATION. INHALATION:RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATI GUE, DROWSINESS, IMPAIRED CO-ORDINATION. INGESTION:NOT A LIKELY ROUTE OF EXPOSURE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION & IRRITATION.

Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:EYES:WASH IMMEDIATELY W/LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN:WIPE OFF W/TOWEL. WASH W/SOAP & WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHAL:REM OVE TO FRESH AIR. ADMINSTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTN. INGEST:DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ADVICE &/OR ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP . WATER SPRAY MAY BE INEFT. WATER MAY BE USED TO COOL CNTNRS TO PVNT PRESS BUILD-UP & EXPLO WHEN EXPOS TO (SUPDAT)

Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY EXPLODE FROM INTERNAL PRESS BUILD UP WHEN EXPOS TO EXTREME HEAT & DISCHARGE CONTENTS. VAP ACCUM CAN FLASH/EXPLODE IF IGNITED. OVEREXP TO(SUPDAT)

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA W/ABSORBENT MATERIAL & PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE & USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE >120F. DO NOT PUNCTURE/INCIN (BURN) CANS. DO NOT SPRAY IN EYE'S. DO NOT TAKE INTERNALLY.

Other Precautions:DO NOT STICK PIN, NAIL/ANY OTHER SHARP OBJECT INTO OPENING OF CAN. SEE PROD LBL FOR ADDNL INFO. SM PRESSURIZED CNTNRS OF FLAMM PRODS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTS W/RESPECT TO CONSTRUCTION, DRAINAGE, CONTROL (SUPDAT)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE UNDER NORMAL USE. AVOID BRTHG VAPS. IN RESTRICTED AREAS, USE NIOSH APPRVD CHEM/MECH FILTERS DESIGNED TO REMOVE COMBINATION OF PARTICLES & VAP. IN CONFINED AREAS, USE NIOSH APPRVD AIR LINE TYPE RE SP/HOOD. NIOSH SCBA IS REQD FOR (SUPDAT)

Ventilation:SUFFICIENT TO PVNT INHAL OF SOLV VAPS. GEN DILUTION &/OR LOC EXHST VENT IN VOL & PATTERN TO KEEP PEL/TLV OF MOST (ING 3)

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS (ING 4)

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET

ANSI DESIGN CRITERIA .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC:EXTREME HEAT. IF WATER IS USED, FOG NOZZ ARE PREF.

EXPLO HAZ:DECOMP PRODS MAY CAUSE HLTH HAZ. SYMPS MAY NOT BE READILY APPARENT. OBTAIN MED ATTN. OTHER PREC:OF IGNIT SOURCES & VENT EXC EPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS. RESP PROT:VAP CONCS ABOVE PEL/TLV LIMS.

===== Physical/Chemical Properties =====

Vapor Pres:SEE INGS

Vapor Density:>1

Evaporation Rate & Reference:>1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W LOCAL, STATE & FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

