

The ServiceMaster Company
The ServiceMaster Way
Downers Grove, IL 60515

SECTION V - HEALTH HAZARD DATA (Cont'd)

Chronic: Prolonged or repeated inhalation of vapors can cause central nervous system depression and permanent nervous system disorders. Prolonged or repeated skin contact can cause irritation or dermatitis. Exposure to elevated concentrations were associated with kidney damage and cancer in male rats only. No similar effects were observed in female rats or mice.

Medical Conditions Generally Aggravated by Exposure: Some pre-existing disorders of the respiratory system, skin, or eyes.

Emergency and First Aid Procedures:
For Inhalation - Move to fresh air.
For Eye Contact - Flush with water for at least 15 minutes, lifting upper and lower lids occasionally. Get medical attention if symptoms persist.
For Ingestion - DO NOT induce vomiting. Get immediate medical attention. Drink several glasses of milk or water. Prevent aspiration. Maintain respiration.
For Skin Contact - N/A

SECTION VI -- REACTIVITY DATA

Stability: Stable
Incompatibility (Materials to Avoid): Strong oxidizers such as permanganate.
Hazardous Decomposition Products: On combustion, carbon dioxide, carbon monoxide, and other unidentified products of combustion.
Hazardous Polymerization: Will not occur.

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled: For large spills, eliminate all possible sources of ignition first. Add absorbent and remove with shovel.
Waste Disposal Method: Dispose of as ignitable hazardous waste. Consign to a waste disposal service. Dispose of all waste in accordance with local, State, and Federal regulations.
Hazardous Waste Classification: D001

SECTION VIII -- SPECIAL PROTECTION INFORMATION

For Handling Product as Supplied: -If TLV is exceeded, use a NIOSH-approved respirator with a cartridge for organic vapors.
Respiratory Protection -Use with sufficient ventilation to maintain exposure below TLV.
Ventilation -NBR or rubber.
Protective Gloves -Not normally needed.
Eye Protection -Not normally needed.
Other Protective Equipment -Not normally needed.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Store in a cool, dry location.
Other Precautions: Empty container may be hazardous. Rinse container thoroughly before disposal.

Prepared By: Kevin T. Wagner
Title: Occupational Safety and Health Coordinator
Date Prepared: November 13, 1996
Supersedes previous form dated: October 3, 1995

SECTION I

Product (Trade Name) - Stainless Steel Cleaner Polish
Manufacturer's Name - The ServiceMaster Company
Address - One ServiceMaster Way, Downers Grove, IL 60515
Emergency Telephone No - 1/800/333-6678
Chemical Name and Synonyms - N/A
Hazardous Family - N/A
Formula - Nonhazardous
DOT Hazard Class - None
DOT ID Number - None

SECTION II -- HAZARDOUS INGREDIENTS

Ingredient	C.A.S. No.	Wt. by %	OSHA PEL	ACGIH TLV-TWA	Other Limit	Listed As Carcinogenic By IARC, NTP, OSHA, ACGIH
Strolem distillate	64742-88-7	40-50	100 ppm*	N/E	N/E	IARC**
* Use exposure limit established for mineral spirits (CAS #8030-30-6) ** See Section V for additional data.						

SECTION III -- PHYSICAL DATA

Boiling Point (°F): initial 212
Vapor Pressure (mm Hg): 7.5
Specific Gravity (H₂O = 1): 0.84
Evaporation Rate (H₂O = 1): 70-75
pH of Concentrate: 1
Dispersible in Water: N/D
Appearance and Odor: Opaque, whitish cream with mineral spirit odor.

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point (Tag, Closed Tester): 110°F
Flammable Limits: LEL UEL
(for petr. distil.): 1.0 N/A

SECTION V -- HEALTH HAZARD DATA

Primary Route(s) of Exposure: Inhalation, skin contact.
Threshold Limit Value: N/D for mixture. See Section II for TLV's of hazardous ingredients.
Effects of Overexposure:
Acute: Irritation of respiratory. Dizziness, headache.
By Inhalation: Burning sensation and irritation of mouth, esophagus, and stomach with nausea, vomiting, headache. Aspiration is indicated by development of a low-grade fever, rapid breathing, cyanosis, and chemical pneumonia.
By Eye Contact: Dryness, possible irritation.

Extinguishing Media: CO₂, foam, dry chemical.
Special Fire Fighting Procedures: Self-contained breathing apparatus and protective clothing should always be worn in fighting fires involving chemicals.
Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot light, other flames, sparks, etc. at locations distant from material handling point.

N/A - Not Applicable N/D - Not Determined N/E - Not Established