

# SAFETY DATA SHEET

## 1. Identification

Product number 022-CP168ASC  
Product identifier CITRUS CREAM DRY DEODORIZER  
Company information AMERICAN SUPPLY COMPANY  
130 W. MARKET ST.  
SALINAS, CA 93901 United States  
Company phone General Assistance 1-630-628-3000  
Emergency telephone US 1-866-836-8855  
Emergency telephone outside US 1-952-852-4646  
Version # 01  
Recommended use Air freshener  
Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1  
Health hazards Serious eye damage/eye irritation Category 2A  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2  
Hazardous to the aquatic environment, long-term hazard Category 2  
OSHA defined hazards Not classified.

Label elements



Signal word Danger  
Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.  
Precautionary statement  
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye/face protection.  
Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Collect spillage.  
Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.  
Hazard(s) not otherwise classified (HNOC) None known.  
Supplemental information None.

## 3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 80
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Other components below reportable levels			1 - 2.5

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician or Poison Control Center immediately. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Immediately take off all contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops or persists. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. In the unlikely event of swallowing contact a physician or poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not induce vomiting without advice from poison control center.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk. Do not direct water at source of leak or safety devices; icing may occur. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
---	---

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Clean contaminated surface thoroughly.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes. Avoid prolonged exposure. Wear self-contained breathing apparatus and protective suit. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

## 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

## Biological limit values

ACGIH Biological Exposure Indices Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
* - For sampling details, please see the source document.				
Exposure guidelines	No Exposure standards allocated.			
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Provide eyewash station.			
Individual protection measures, such as personal protective equipment				
Eye/face protection	Chemical respirator with organic vapor cartridge and full facepiece.			
Hand protection	Wear appropriate chemical resistant gloves.			
Skin protection				
Other	Do not get this material in contact with skin. Wear appropriate chemical resistant gloves. Wear suitable protective clothing.			
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	Do not get this material in contact with eyes. When using, do not eat, drink or smoke. Do not get this material in contact with skin. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

## 9. Physical and chemical properties

### Appearance

Physical state	Gas. Form Aerosol.
Color	Pale yellow
Odor	Characteristic.
Odor threshold	Not available.
pH	Not applicable estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.9 % estimated
Flammability limit - upper (%)	9.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 70 psig @70°F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.693 estimated estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

### Information on toxicological effects

Acute toxicity	Acute LD50: 29145 mg/kg, Rat, Dermal Narcotic effects.
----------------	---

Product	Species	Test Results
10 OZ ASC CITRUS CREAM LB 12PK (CAS Mixture)		
Acute Dermal LD50	Rat	29145 mg/kg
Inhalation LC50	Rat	105 mg/l/4h
Oral LD50	Rat	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute Dermal LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l

Components	Species	Test Results
Oral LD50	Rat	5800 mg/kg 2.2 ml/kg
Butane (CAS 106-97-8) Acute Inhalation LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6) Acute Inhalation LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Not expected to be hazardous by OSHA criteria. Not applicable.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.
Carcinogenicity	Not expected to be hazardous by WHMIS criteria. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	Not expected to be hazardous by OSHA criteria.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause lung injury.

## 12. Ecological information

Ecotoxicity	LC50: 8050 mg/L, Fish, 96.00 Hours EC50: 19608 mg/L, Daphnia, 48.00 Hours Toxic to aquatic life with long lasting effects.
-------------	--

Product	Species	Test Results
10 OZ ASC CITRUS CREAM LB 12PK (CAS Mixture)		
Aquatic		
Crustacea	EC50 Daphnia	19608 mg/L, 48 Hours
Fish	LC50 Fish	8050 mg/L, 96 Hours
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24

Butane 2.89

Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)

U002

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

#### DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) Packing 2.1

group Environmental Not applicable.

hazards Yes

ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s) Packing group	2.1
Environmental hazards	Not applicable.
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code      This substance/mixture is not intended to be transported in bulk.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.



## 15. Regulatory information

US federal regulations      This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)  
Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)  
Acetone (CAS 67-64-1)      Listed.

SARA 304 Emergency release notification  
Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)  
Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories      Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

SARA 302 Extremely hazardous substance  
Not listed.

SARA 311/312 Hazardous chemical      No

SARA 313 (TRI reporting)  
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List  
Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)      Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number  
Acetone (CAS 67-64-1)      6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))  
Acetone (CAS 67-64-1)      35 %WV

DEA Exempt Chemical Mixtures Code Number  
Acetone (CAS 67-64-1)      6532

US state regulations

US. Massachusetts RTK - Substance List  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

US. Rhode Island RTK  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

## US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date 01-06-2015

Version # 01

**Disclaimer**  
We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information**  
Product and Company Identification: Product Uses  
Physical & Chemical Properties: Multiple Properties  
Physical and chemical properties: Appearance